

The Good, The Bad & The Ugly of Airport Lighting Maintenance



YOU CANNOT MANAGE WHAT YOU DO NOT MEASURE

**THE GOOD
AND THE BAD
AND THE UGLY**

Performed by:

**DANISH NATIONAL SYMPHONY ORCHESTRA
DANISH NATIONAL CONCERT CHOIR**

Soprano:

CHRISTINE NONBO ANDERSEN

Conducted by:

SARAH HICKS

Who are we?

1. Airport Electricians
2. Consultants & Consultants
3. Contractors and Installers
4. Equipment Manufacturers
5. Government
6. Pilots & Passengers



Safety & Compliance

- When you get on a plane do you expect it to be properly maintained at all times?
- Do you expect the Crew to be Competent and Trained?
- Do you expect ATC to be Competent and Trained?
- Do you expect the ILS to be properly maintained?
- Do you expect the visual aids (lights, signs and PAPI's) to be compliant



There are no barriers to success

- Maintenance requirements are clearly documented in AC 150-5340/26c
- Processes and procedures exist to support their implementation (SMS)
- Tools and Equipment have been developed to support installation and maintenance in compliance with these standards
- Competent Electricians have been trained to execute their tasks necessary to maintain compliant lighting



But are there?

- Recently I was asked, on the topic of serviceability of lighting systems:
 - What are the levels below where operations should not continue and;
 - What are the considerations to take in to account when setting this levels and;
 - What should we do when the levels are reached?
 - Is it left to the Pilots discretion to decide whether to take-off or land?



And the answer is:

1. All national and International Standards specify airfield lighting serviceability levels for CAT I/II/III
2. Since the light levels are mandatory, a failure to meet the Standard is a regulatory breach and a NOTAM should be published
3. If points 1 and 2 are implemented then the pilot will be constrained to take the appropriate decision by the licensing regulations. This will vary by aircraft, airport and qualifications of the pilot. This decision is not discretionary.



Is your airfield lighting compliant?

- Ask the Airport Manager
 - I would expect the answer to be yes
 - The next question is "how do you know"
 - The answer will be along the lines "I have a SMS in place with people who take care of it for me." But how do they know?
- Ask a FAA inspectors
 - They never ask for photometric measurements
 - They tell me they can only measure what they can e.g. Signs and markings for physical compliance
 - They have no means of measuring an airports safety critical visual aids AND VERY FEW AIRPORTS HAVE MEASUREMENT TOOLS



So what?

Does anybody care?

Why should they care?

- The aviation industry prides itself on their being no single point of failure in the system that could, on its own, cause a fatal accident. Runway lighting is an important part of this system, especially in low visibility conditions
- A Boeing study into aviation fatal accidents found that the final approach and landing stages of flights accounted for 60%
- More than 90% of these accidents occurred in low visibility
- What is the difference between good visibility and bad visibility?
- You can't see the lights!





Airport Lighting Maintenance - Airport 4.0

and migration towards Performance based and Predictive Maintenance techniques, tools and processes :

Installation & Material

- ☐ Correctly selected equipment
- ☐ Equipment correctly installed
- ☐ Correct acceptance criteria

Maintenance Processes & Procedures

- ☐ Scheduled inspections & Tests
- ☐ Equipment kept in good condition
- ☐ Correctly adjusted equipment

Tools, Test Equipment and Product Support

- ☐ Correct tools & calibrated test equipment
- ☐ Adequate working space & storage
- ☐ Product Training and After Sales Support

Electricians

- ☐ Competence
- ☐ Training
- ☐ Access to runways & taxiways

Measure – Maintain – Monitor - Manage



Installation & Material

- ❑ Correctly selected equipment
 - Involve the Airfield Electricians
 - Ensure that the equipment is compatible with other systems or equipment
 - Define equipment requirements
- ❑ Equipment correctly installed
 - Process
 - Tools
 - Training
 - Competence
 - Management
- ❑ Correct acceptance criteria
 - Define appropriate acceptance criteria



Maintenance Processes & Procedures

- ❑ AC No: 150/5340-26C

This advisory circular (AC) provides recommended guidelines for maintenance of airport visual aid facilities.

Use of this AC is mandatory for all projects funded with federal grant monies through the Airport Improvement Program (AIP) and with revenue from the Passenger Facility Charges (PFC) Program.



Tools, Test Equipment & Product Support

- ❑ Adequate working space & storage
 - availability of appropriate and sufficient physical room and organizational capacity within a workspace to facilitate efficient and safe operations
- ❑ Correct tools & calibrated test equipment
 - using the correct tools and calibrated test equipment is essential for ensuring precision, safety, and reliability
 - calibrating test equipment contributes significantly to the accuracy and effectiveness of work processes.
- ❑ Product Training and After Sales Support
 - product training and after-sales support are integral parts of customer service. They ensure that customers not only understand how to use the product effectively but also receive assistance and support whenever they encounter issues



Electricians

- ❑ Competence
 - the necessary knowledge, skills, training, and attitude to perform specific tasks or make decisions safely and effectively.
- ❑ Training
 - the process of teaching, developing skills, and imparting knowledge to individuals or groups to improve their performance, competence, and abilities in a specific area
- ❑ Access to runways and taxiways
 - airports must establish procedures whereby electricians can routinely access runways and taxiways to perform scheduled maintenance tasks



Light Fixture Maintenance Maintaining Proper Light Output per FAA AC 150/5340-26C


Intensity Checks/Photometric Testing

Regular photometric measurements are the only practical way of determining if the lights are emitting the specified amount of light and for determining misalignment errors.

Any runway light fixture exhibiting a light output of less than 70% of the minimum output required when operated at maximum intensity per AC 150/5345-46, Specification for Runway and Taxiway Light Fixtures, is ineffective for high background brightness, low visibility conditions and should be targeted for cleaning or maintenance.



Light Fixture Maintenance Maintaining Proper Light Output per FAA AC 150/5340-26C






What Affects Photometric Results?




- Dirt & Contamination
- Lying Water
- Warm-up period
- Variation of lumen output
- Current
- Fixture alignment
- Ambient Light
- Color
- Condition of Lens
- Level of seating / plough ring
- Fixture Design / manufacturing issues



Sign Measurement


Sign Test Report					
		<p>The Lethbridge Airport Signs / Signs / < - A From: 9/18/2023 To: 9/25/2023 Report Prepared: 9/25/2023 2:17:41 PM (Week 39)</p>			
Test Details		Parameter	Measured	Reference	Result
Light Test ID:	1_2	Sign Face			
Date/Time:	9/23/2023 9:42:59 AM	Mean L (cd/m ²)	192.3	>= 150.0	OK
Area:	Signs	Max L (cd/m ²)	250.8		
Zone:	Signs	Min L (cd/m ²)	98.6		
Location:	< - A	CIE x, CIE y	0.486, 0.508		
System:	YB	Colour	Yellow	Yellow	OK
Sign No.:	1/2	L Ratio Adjacent	2.14	<= 1.5	Warning
Sign Type:	< - A	L Ratio Global	2.54	<= 5.0	OK
Colour:	Yellow	L Ratio Red/White	0.00	>= 0.1 & <= 0.2	
Width/Height:	1.8/0.6 m	Face Characters			
Latitude:	49.630883	Mean L (cd/m ²)			
Longitude:	-112.790902	Max L (cd/m ²)			
Operator Name:		Min L (cd/m ²)			
		CIE x, CIE y			
		Colour			
		Side Characters			
		Mean L (cd/m ²)			
		Max L (cd/m ²)			
		Min L (cd/m ²)			
		CIE x, CIE y			
		Colour			
		Test Result			
		Warning			

Mandatory Sign
















Sign Test Report																																																																																																	
<div><div></div><div><div>The Lethbridge Airport</div><div>Signs / Signs / 13-31</div><div>From: 9/18/2023 To: 9/25/2023</div><div>Report Prepared: 9/25/2023 2:22:17 PM (Week 39)</div></div><div></div></div>																																																																																																	
Test Details	<table><thead><tr><th>Parameter</th><th>Measured</th><th>Reference</th><th>Result</th></tr></thead><tbody><tr><td colspan="4">Sign Face</td></tr><tr><td>Mean L (cd/m²)</td><td>37.0</td><td>>= 30.0</td><td>OK</td></tr><tr><td>Max L (cd/m²)</td><td>47.1</td><td></td><td></td></tr><tr><td>Min L (cd/m²)</td><td>19.8</td><td></td><td></td></tr><tr><td>CIE x, CIE y</td><td>0.663, 0.316</td><td></td><td></td></tr><tr><td>Colour</td><td>Red</td><td>Red</td><td>OK</td></tr><tr><td>L Ratio Adjacent</td><td>1.95</td><td><= 1.5</td><td>Warning</td></tr><tr><td>L Ratio Global</td><td>2.38</td><td><= 5.0</td><td>OK</td></tr><tr><td>L Ratio Red/White</td><td>0.13</td><td>>= 0.1 & <= 0.2</td><td>OK</td></tr><tr><td colspan="4">Face Characters</td></tr><tr><td>Mean L (cd/m²)</td><td>280.5</td><td>>= 300.0</td><td>Fail</td></tr><tr><td>Max L (cd/m²)</td><td>340.2</td><td></td><td></td></tr><tr><td>Min L (cd/m²)</td><td>195.0</td><td></td><td></td></tr><tr><td>CIE x, CIE y</td><td>0.393, 0.414</td><td></td><td></td></tr><tr><td>Colour</td><td>White</td><td>White</td><td>OK</td></tr><tr><td colspan="4">Side Characters</td></tr><tr><td>Mean L (cd/m²)</td><td></td><td></td><td></td></tr><tr><td>Max L (cd/m²)</td><td></td><td></td><td></td></tr><tr><td>Min L (cd/m²)</td><td></td><td></td><td></td></tr><tr><td>CIE x, CIE y</td><td></td><td></td><td></td></tr><tr><td>Colour</td><td></td><td></td><td></td></tr><tr><td colspan="4">Test Result</td></tr><tr><td colspan="4">Fail</td></tr></tbody></table>	Parameter	Measured	Reference	Result	Sign Face				Mean L (cd/m ²)	37.0	>= 30.0	OK	Max L (cd/m ²)	47.1			Min L (cd/m ²)	19.8			CIE x, CIE y	0.663, 0.316			Colour	Red	Red	OK	L Ratio Adjacent	1.95	<= 1.5	Warning	L Ratio Global	2.38	<= 5.0	OK	L Ratio Red/White	0.13	>= 0.1 & <= 0.2	OK	Face Characters				Mean L (cd/m ²)	280.5	>= 300.0	Fail	Max L (cd/m ²)	340.2			Min L (cd/m ²)	195.0			CIE x, CIE y	0.393, 0.414			Colour	White	White	OK	Side Characters				Mean L (cd/m ²)				Max L (cd/m ²)				Min L (cd/m ²)				CIE x, CIE y				Colour				Test Result				Fail			
Parameter	Measured	Reference	Result																																																																																														
Sign Face																																																																																																	
Mean L (cd/m ²)	37.0	>= 30.0	OK																																																																																														
Max L (cd/m ²)	47.1																																																																																																
Min L (cd/m ²)	19.8																																																																																																
CIE x, CIE y	0.663, 0.316																																																																																																
Colour	Red	Red	OK																																																																																														
L Ratio Adjacent	1.95	<= 1.5	Warning																																																																																														
L Ratio Global	2.38	<= 5.0	OK																																																																																														
L Ratio Red/White	0.13	>= 0.1 & <= 0.2	OK																																																																																														
Face Characters																																																																																																	
Mean L (cd/m ²)	280.5	>= 300.0	Fail																																																																																														
Max L (cd/m ²)	340.2																																																																																																
Min L (cd/m ²)	195.0																																																																																																
CIE x, CIE y	0.393, 0.414																																																																																																
Colour	White	White	OK																																																																																														
Side Characters																																																																																																	
Mean L (cd/m ²)																																																																																																	
Max L (cd/m ²)																																																																																																	
Min L (cd/m ²)																																																																																																	
CIE x, CIE y																																																																																																	
Colour																																																																																																	
Test Result																																																																																																	
Fail																																																																																																	
<div><div>Light Test ID: 3_4</div><div>Date/Time: 9/23/2023 9:53:01 AM</div><div>Area: Signs</div><div>Zone: Signs</div><div>Location: 13-31</div><div>System: RW</div><div>Sign No.: 1/2</div><div>Sign Type: 13-31</div><div>Colour: Red</div><div>Width/Height: 1.8/0.6 m</div><div>Latitude: 49.629806</div><div>Longitude: -112.791845</div><div>Operator Name: Richard Gore</div></div> <div></div>	<div>1</div>																																																																																																

What affects the sign results?


- Age of the sign board
- Cleanness of the sign board inside and outside
- Age of the bulbs/LED strips/fluorescent tube
- Damage to the sign face (environmental and physical)
- Obstacles, such as growing vegetation
- Sign design issues including retrofit




PAPI Measurement


PAPI Status (180 Days)			
Zone	% OK	Reports	Last Inspection
 PAPI06	 50%		9/23/2023
 PAPI13	 0%		9/22/2023
 PAPI24	 75%		9/23/2023
 PAPI31	 50%		9/23/2023
 All	 44%		9/23/2023


PAPI 24-C

Test Details		Parameter	Measured	Reference	Result
Light Test ID:	11_14	Minimum Intensity White (cd)	75621.1	> 30000.0	OK
Date/Time:	9/23/2023 7:38:36 AM	Minimum Intensity Red (cd)	16609.8	> 15000.0	OK
Area:	PAPI	Ratio Min White/Red	4.55	>= 2.0 & <= 6.5	OK
Zone:	PAPI24	Vertical Angle (deg)	3°08'32"	3°10'00" ± 3'	OK
Location:	PAPI24-C	White Colour CIE _x , CIE _y	0.435, 0.399	White	OK
System:	PAPI24	Red Colour CIE _x , CIE _y	0.670, 0.322	Red	OK
Light No.:	3/4	Mean Intensity White (cd)	78624.2		
Light Type:	PAPI (Precision Approach Path Indicator)	Mean Intensity Red (cd)	17991.6		
		Maximum Intensity (cd)	87079.9		
Manufacturer:		Horizontal Angle (deg)	0°24'00"	0°00'00" ± 12'	OK
Fitting Type:		Filter Alignment	Well Aligned		OK
Colour:	White/Red				
Latitude:	49.628565				
Longitude:	-112.793129				
Operator Name:	Richard Gore				
Optics Quality: Medium					
All colour transitions could be estimated.					
Test Result					
Pass					
					





PAPI 13-C

Test Details		Parameter	Measured	Reference	Result
Light Test ID:	7_2	Minimum Intensity White (cd)	26440.2	> 30000.0	Fail
Date/Time:	9/22/2023 5:10:24 AM	Minimum Intensity Red (cd)	6691.8	> 15000.0	Fail
Area:	PAPI	Ratio Min White/Red	3.95	>= 2.0 & <= 6.5	OK
Zone:	PAPI13	Vertical Angle (deg)	3°07'48"	3°10'00" ± 3'	OK
Location:	PAPI13-C	White Colour CIE _x , CIE _y	0.443, 0.400	White	OK
System:	PAPI13	Red Colour CIE _x , CIE _y	0.662, 0.328	Red	OK
Light No.:	3/4	Mean Intensity White (cd)	26992.7		
Light Type:	PAPI (Precision Approach Path Indicator)	Mean Intensity Red (cd)	7472.0		
		Maximum Intensity (cd)	28920.1		
Manufacturer:		Horizontal Angle (deg)	0°00'00"	0°00'00" ± 12'	OK
Fitting Type:		Filter Alignment	Well Aligned		OK
Colour:	White/Red				
Latitude:	49.635545				
Longitude:	-112.796727				
Operator Name:	Richard Gore				
Optics Quality: Medium					
All colour transitions could be estimated.					
Test Result					
Fail					
					



What affects the PAPI lamp unit results?

- Vertical and horizontal alignment of the PAPI unit (requires accurate clinometer)
- Age and condition of the bulbs/reflectors/lenses/filters
- Internal and external cleanness
- Misaligned filters
- Vegetation
- Physical damage



Airport CMMS Dashboard

